Residential Energy Storage System (High Voltage & Stackable)



SOL-25-10HT





High Efficiency

Max. efficiency 94%



Easy installation

50 Kg Battery modules



Safety and Reliability

Lithium-ion phosphate battery cells



System Integration

Integrated design, plug and play, no compatibility issues

Product Introduction

Scalable from 20 kWh to 30 kWh

Self-Consumption Optimization

The motherboard intelligently ADAPTS to voltage

Integrated with inverter to avoid the compatibility problem

LFP battery, safest and long cycle life

Stackable design, effortlessly installation

High voltage solution makes higher conversion energe fficiency

Support 3 Phase Output

[分] Battery Module

- 5.12 kWh per Module
- Modular and Stack Installation Design to simplify the maintenance
- Main board self-adjustable to voltage

Residential Energy Storage System (High Voltage & Stackable)



Flexible, Efficient, Simple Plug Connection No Additional Wiring Required Easily Adapts to New Requirements Requirements Flexible, Efficient, Simple ### Connection Extend Anytime Easily Adapts to New Requirements Power for Every Application

| Inverter | SOL10KH-T |
|---------------------------------------|--|
| Maximum Photovoltaic Input Power | 15KW |
| Rated Photovoltaic DC Input Voltage | 620V |
| MPPT Operating Voltage Range | 200-950V |
| MPPT Quantity | 2 |
| Maximum Photovoltaic Input Current | 15A/15A |
| Rated Output Power to Gird | 10KW |
| Rated Voltage | 3L/N/PE; 220/380V;230/400V;240/415V |
| Frequency of Grid | 50/60Hz |
| Maximum Output Current to Grid | 16.5A |
| Battery Voltage Range | 135-750V |
| Max. Battery Charge/Discharge Current | 25A/25A |
| Rated Output Power to Load | 10KW |
| Rated Output Voltage to Load | 3L/N/PE;220/380V;230/400V;240/415V |
| Maximum Output Current to Load | 16.5A |
| Battery Parameters | |
| Usable Energy (kWh) | 25.6 |
| Number of Modules | 6 |
| Cell Type | LFP(LiFePO4) |
| Nominal Voltage (V) | 256 |
| Operating Voltage Range (V) | 224~292 |
| Nominal Dis- / Charge Current (A) | 50 |
| Operating Temperature Range (℃) | Charge:0~50°C; Discharge: -10~50°C |
| Communication | CAN/RS485 |
| Weight (kg) | 300±1 |
| Dimensions (W x D x H mm) | 680*429*1470 mm |
| Ingress Protection Rating | IP55 |
| Round-Trip Efficiency | ≥95% |
| Applications | on/off-grid energy storage/off-grid power backup |
| Compatible Inverters | PYLON, Sacolar, Deye, Growatt, Sofar, Voltronic, LUX, Schneider, Afore, Sinexcel, SUNGROW, Sorotec, GoodWe, KSTAR, Srne, Must, Megarevo, Sol-Ark, INVT, Aiswei, TBB, SAKO, Solis, SMA, Victron, SMK, BlueSun |