## **Lithium Iron Phosphate Battery**

LFELI-48150 (48V150Ah)



## Features Of LiFePO4 Battery

- Safe Lithium Iron Phosphate Technology
- Safe to use Low self-discharge rate

Physical Dimension-mm

 $442 \pm 1$ 

[<u>76.8</u>±]

550±1

- Excellent high temperature performance
- · High cycle times and long life
- High energy density and conversion efficiency
- · Environmentally friendly without any heavy metals
- High-performance BMS battery management system
- · Easy to install, 19-inch cabinet or wall-mounted installation

## 

## **Typical Applications**

- Access Network Equipment
- Remote Switching Offices
- Mobile Communication Equipment
- Transmission Equipment
- Satellite Ground Stations
- Microwave Communication Equipment
- · Communication field as backup power supply

Item	Parameters
Model	LFELI-48150
Rated Capacity (5HR)	150 Ah
NominalVoltage	48V
Discharge Ending Voltage	40.5V
Charging Limited Voltage	54V
Max. Charging/Discharge Current	100A (Maximum Overcurrent 150A)
Weight	Approx. 59KG
Energy	7200Wh
Display	With LCD display
Max. number of parallel connection	40
Dimensions (W*D*H) mm	442*550*177
Design Life	20 years
Cycle Life	6000 cycles
IP Class	IP30
Case Material	SPCC
Operating Temperature	Charging: 0 to +45°C, Discharging: -10 to +55°C, Storage: -20 to +60°C
Terminal	M6

Constant Current Discharge Table (Amperes) at 25°C							
Voltage Time	1.5h	3 h	6 h	8 h	10 h		
End of discharge voltage 40.5V	100A	50A	25A	18.75A	15A		

Constant Power Discharge Table (Watts) at 25°C							
Voltage Time	1.5 h	3 h	6 h	8 h	10 h		
End of discharge voltage 40.5V	4800W	2400W	1200W	900W	720W		

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. ©LEOCH.All rights reserved.Trademarks and logos are the properly of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice E&OE.