

# Residential Energy Storage Battery (Wall-mounted)



LW25.6-100



**High Efficiency**

Max. efficiency 95%



**Eco-Friendly**

Clean energy



**Long Lifespan**

Sustainable long cycles



**Built-in BMS**

Charge & discharge protection

## Product Introduction



Up to 15 groups of parallel connections,  
flexible capacity expansion



LED display for voltage, current, temperature,  
convenient for users to query



Compatible with mainstream inverters in the  
market, providing more options



Built-in BMS provides multiple protection  
functions

Item	Parameters
Specifications and models	<b>LW25.6-100</b>
Nominal voltage	25.6V
Nominal capacity	100Ah
Maximum charge/ discharge current	100A/100A
Discharge voltage/Maximum charge	21.6 V/29.2 V
Weight	29kg
Dimensions(W×D×H)(mm)	375x500x165
Cycle life	6000 cycles @80% DOD
Max number of parallel connections	15
Self-discharge (month)@25°C	≤3%
BMS communication types	RS485/RS232/CAN
Cooling Mode	Free Cooling
IP Class	IP54
Display Fuction	LCD Display
Design Life	15 Years
Storage Temperature	-20°C to 60°C
Operate Temperature	charge: 0°C to 45°C; discharge: -10°C to 55°C
Relative Humidity	5% to 95%
Working Pressure	61kPa~113kPa