## **Lithium Iron Phosphate Battery**

LFELI-48100ZN (48V100Ah)




## Features Of LiFePO4 Battery

- · Safe Lithium Iron Phosphate Technology
- · Safe to use Low self-discharge rate
- · Excellent high temperature performance
- · High cycle times and long life
- · High energy density and conversion efficiency
- · Environmentally friendly without any heavy metals
- High-performance BMS battery management system
- Easy to install, 19-inch cabinet or wall-mounted installation



## Physical Dimension-mm



## **Typical Applications**

- · Access Network Equipment
- · Remote Switching Offices
- Mobile Communication Equipment
- · Transmission Equipment
- · Satellite Ground Stations
- · Microwave Communication Equipment
- · Communication field as backup power supply

Item	Parameters
Model	LFELI-48100ZN
Rated Capacity (5HR)	100 Ah
Nominal Voltage	48V
Discharge Ending Voltage	40.5V
Charging Limited Voltage	54V
Max. Charging/Discharge Current	100A
Weight	Approx. 40KG
Energy	4800Wh
Display	Without LCD display
Max. number of parallel connection	CAN communication supports 32 parallel groups
Dimensions (W*D*H) mm	442*450*133
Design Life	20 years
Cycle Life	6000 cycles
IP Class	IP30
Case Material	SPCC(Aluminum Alloy panel)
Operating Temperature	Charging: 0 to +45°C, Discharging: -10 to +55°C, Storage: -20 to +60°C
Terminal	M6

Constant Current Discharge Table (Amperes) at 25°C								
Voltage Time	1 h	2 h	3 h	5 h	10 h			
End of discharge voltage 40.5V	100A	50A	33.3A	20A	10A			

Constant Power Discharge Table (Watts) at 25°C							
Voltage Time	1 h	2 h	3 h	5 h	10 h		
End of discharge voltage 40.5V	4800W	2400W	1600W	960W	480W		