


# Residential Energy Storage Battery (Rack-mounted)



LR51.2-200



**Compact Size**

Minimum the footprint



**Eco-Friendly**

Clean energy



**Long Lifespan**

Sustainable long cycles



**Built-in BMS**

Charge & discharge protection

## Product Introduction



Up to 15 groups of parallel connections,  
flexible capacity expansion



LED display for voltage, current, temperature,  
convenient for users to query



Compatible with mainstream inverters in the  
market, providing more options



Built-in BMS provides multiple protection  
functions

Item	Parameters
Model	LR51.2-200
Rated Capacity (5HR)	200 Ah
Nominal Voltage	51.2 V
Energy	10.24KWh
Discharge Ending Voltage	43.2 V
Charging Limited Voltage	57.6 V
Max. Charge/Discharge Current	150 A
Weight	Approx. 84 Kg
Display	With display screen
Protocol	RS485/RS232/CAN
Max number of parallel connections	15
Dimensions (W*D*H) mm (inches)	442 *590 *244
Design life	More than 15 years
Cycle Life	More than 6000 cycles @ 80% DOD
IP Class	IP31
Case Material	SPCC
Operating Temperature	Charging: 0 to +45°C    Discharging: -10 to +55°C    Storage: -20 to +60°C
Compatible Inverters	PYLON, Sacolar, Deye, Growatt, Sofar, Voltronic, LUX, Schneider, Afore, Sinexcel, SUNGROW, Sorotec, GoodWe, KSTAR, Srne, Must, Megarevo, Sol-Ark, INVT, Aiswei, TBB, SAKO, Solis, SMA, Victron, SMK, BlueSun