Residential Energy Storage System (Low Voltage & Stackable) SOL-5-5.6LS





Max. efficiency 94%

50 Kg Battery modules



Lithium-ion phosphate battery cells

Integrated design, plug and play, no compatibility issues

Product Information



Self-Consumption Optimization 191



Maximum flexibility for any applications with up to 12

modules connected in parallel




Integrated with inverter to avoid the compatibility problem



LFP battery, safety and long cycle life

Stackable design, effortlessly installation



[4] Battery Module

- 5.12 kWh per Module
- · Modular and Stack Installation Design to simplify the maintenance
- · Connect up to 12 module in parallel for a maximum size of 60 kWh



High Power

Power for Every

Application

Flexible, Efficient, Simple



Technical Parameters		
Inverter	SOL-5.6KL-S	
Rated Power	5600W	
Maximum PV Array Open Circuit voltage	500VDC	
MPPT Voltage Range	120-450V	
Nomial Output Voltage	220/230/240VAC	
Output Voltage Range	184-265VAC	
Nominal Output Current	25.5A/24.3A/23.3A	
Efficiency	Up to 93.5%	
Grid Output Voltage Range	120-280VAC	
Grid Frequency	50/60Hz(Auto Sensing)	
Maximum AC Charge Current	120A	
Maximum Solar Charge Current	120A	
Nominal DC Voltage	48VDC	
Battery Model	SOL-51.2/100-L	
Combination Method	16S1P	
Rated Capacity	Typical	100Ah
	Minimum	98Ah
Rated Voltage	51.2V	
Limited Discharge Voltage	43.2V	
Limited Charge Voltage	57.6V	
Internal Resistance(single battery pack)	≤20mΩ	
Max Continuous Charging Current	100A	
Max Continuous Discharging Current	100A	
Operation Temperature Range	Charge:0~50 ℃/ Discharge: -10~50 ℃	
Storage Temperature Range	-20~+60°C,Recommend: ≤60±25%RH storage humidity	
Single Module Size/weight	680*429*215mm /50Kg±1Kg	
Overall Size/weight	680*429*540mm /85Kg±1Kg	
Compatible Invertore	PYLON, Sacolar, Deye, Growatt, Sofar, Voltronic, LUX, Schneider, Afore,	

Compatible Inverters

Sinexcel, SUNGROW, Sorotec, GoodWe, KSTAR, Srne, Must, Megarevo, Sol-Ark, INVT, Aiswei, TBB, SAKO, Solis, SMA, Victron, SMK, BlueSun