


DT SERIES FLOODED BATTERY DT-L16 (6V420Ah)


















Designed in compliance with applicable BCI standard. Tested in compliance to BCI standard.

Leoch International Technology Ltd. www.leoch.com

Leoch Batteries Pte Ltd www.leoch.sa

CHARACTERISTICS

Item		Specifications
Voltage		6V
Dimension	Length	296mm (11.7inches)
	Width	176mm (6.93inches)
	Container Height	402mm (15.8inches)
	Total Height	425mm (16.7inches)
Approx Weight		52kg (114.6lbs)
Terminal		DT(5/16")
Container Material		PP
Rated Capacity	20HR	420Ah
	5HR	344Ah
Reserve Capacity	25A	850min
	75A	220min


GENERAL FEATURES

- · Long cycle service life, strong recovery ability of deep discharge
- · Low risk of thermal runaway, easy maintenance
- High energy, low internal resistance, low self-discharge
- · Reliable sealing structure ensures no leakage during use
- · Special design and structure increase battery performance
- · The special alloy improves the corrosion resistance of the plate increases the service life and good deep discharge performance

APPLICATIONS

- · Electric vehicle
- Golf cart
- AWP
- · Sightseeing bus
- · Cleaning equipment

- Marine&RV



Leoch Battery Corporation m www.leoch.us

Leoch Europe S.A. www.leoch.eu

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-DT-L16-PD-EN-V1.0-20230830