

Lithium Battery

LFP1233



Features Of LiFePO4 Battery

- Ultra light weight
- High integration, small size, high energy density
- Eco-friendly clean energy
- Long lifespan sustainable
- High efficiency

Application scenarios

- Electric vehicles, Electric mobility
- Solar/wind energy storage system
- Telecommunication
- Medical equipment
- Lighting

Specification

Nominal Voltage	12.8V
Working Voltage	10-14.6V
Nominal Capacity	33Ah
Energy	422.4Wh
Self Discharge	≤3% Per Month
IP Grade	IP65
Positive material	Lithium ironphosphate
Cell type	Cylindrical
Combination method	3.4Ah,10P4S
Weight	ABOUT 4.0KG
Dimension LxWxH	L175W166H125mm
Fixed size	NO
Terminal Type	T3
Shell type	ABS
Handle	No
Storage Temp. short term	-20-50°C
Storage Temp. long term	-20-25°C
Cycle Life	5000 cycles
Heating function	No
Cooling type	No
Insulation	20MΩ/1000VDC, @25±5°C, RH50%
Connection options	Single Use



Charging

Recom. Charging Current	11.22A
Upper limit voltage	14.6V
Charging Temp. Range	0~45°C

DisCharging

Max Continuous Discharge	30.0A
Max Discharge current	150A@16ms
Lower limit voltage	10.0V
BMS Voltage Recovery	11.2V
Discharge Temp. Range	-20-60°C

Function (optional)

(CAN/RS485), Bluetooth, Screen, Charger

Physical Dimension-mm

