

### Physical Specification




Nominal Voltage	12V	
Nominal Capacity (10Hr)	3.0 Ah	
Dimension	Length	112±2mm (4.45 inches)
	Width	69±2mm (2.76 inches)
	Container Height	85±2mm (3.35 inches) Total
	Height (with Terminal)	82±2mm (3.35 inches)
Weight	Approx 0.65kg(1.43lbs)	

- \* Motorcycle Li-ion battery
- \* Maintenance-free
- \* Real-time protection (overcharge, over-discharge, over-temperature) and energy balance of battery system through BMS
- \* Powerful 105 cold cranking amps
- \* Shipped pre-charged and ready to install
- \* Replaces YTX4L-BS、YTZ5S-BS、YTX5L-BS、YTZ6-BS、YTX7L-BS battery



### Electrical Specification

Rated Capacity	0.1C rate (0.35A)	3.50Ah
	0.5C rate (1.75A)	3.50Ah
	10C rate (35.0A)	3.15Ah
	60C rate(180.0A)	3S
Capacity affected by Temperature	40 °C (104 °F)	98%
	25 °C (77 °F)	100%
	0 °C ( 32 °F)	85%
	-20 °C ( -4 °F)	60%
Self Discharge	Approximately 1.5% per month (25°C (77°F))	
Charging Methods	Constant-Voltage Charge: Full Charge Initial charging current: less than 3.5A Voltage: 14.40 V ~ 14.60 V at 25 °C (77 °F)	



Dimensions (mm)

### Curve Specification

