

Starter batteries for motorcycles

MKS-1203MC-B 12.8V3.0Ah

Physical Specification


Nominal Voltage		12.8V
Nominal Capacity (10Hr)		3.0 Ah
Dimension	Length	150±2mm (5.91 inches)
	Width	87±2mm (3.43 inches)
	Container Height	105±2mm(4.13 inches) Total
	Height (with Terminal)	105±2mm (4.13 inches)
Weight	Approx 0.633kg (1.40lbs)	

- * Motorcycle Li-ion battery
- * Maintenance-free
- * Real-time protection (overcharge, over-discharge, over-temperature) and energy balance of battery system through BMS
- * Powerful 90 cold cranking amps
- * Shipped pre-charged and ready to install
- * Replaces YTX9-BS/YTR9-BS battery



Electrical Specification

Rated Capacity	0.1C rate (0.3A)	3.0Ah
	0.5C rate (1.5A)	3.0Ah
	10C rate (30.0A)	2.7Ah
	30C rate (90.0A)	3S
Capacity affected by Temperature	40 °C (104 °F)	98%
	25 °C (77 °F)	100%
	0 °C (32 °F)	85%
	-20 °C (-4 °F)	60%
Self Discharge	Approximately 1.5% per month (25°C (77°F))	
Charging Methods	Constant-Voltage Charge: Full Charge Initial charging current: less than 0.8A Voltage: 14.40 V ~ 14.60 V at 25 °C (77 °F)	



Dimensions (mm)

Curve Specification

